

2. WINDING, TEXTURIZING and TWISTING MACHINES

1.1 – HANK TO CONE WINDERS

2.1.09.075

Hank to Cone Corghi winder model E4- – y.o.c. 2001

4 heads - 6" traverse - conical package 5°57 - max. diam. 290 mm

One motor per head with slow start

Hank 240 mm - circumference min. 1100 max 1800

Potentiometer for speed adjustment : from 120 to 700 m/m

Soft start with acceleration ramp 15 sec.

Head stop at required diameter

Slub-catcher, waxing, splicer



2.1.09.082

Hank to Cone Corghi winder model ICL – y.o.c. 1995

24 heads - 6" traverse - conical package 5°57-max. diam. 290 mm

Stop at diameter

One motor per head with slow start

Soft start with acceleration ramp 15 sec.

Hank 340 mm - circumference min. 1100 max 1800

Potentiometer for speed adjustment : from 150 to 700 m/m

30% automatic reduction speed per position

Head stop at required diameter

Mechanical slub-catcher with micrometer adjustment

Waxing device

Hank length adjustable per each position



2. WINDING, TEXTURIZING and TWISTING MACHINES

1.1 – HANK TO CONE WINDERS

2.1.09.083

No. 2 Hank to Cone Corghi winders model ICL y.o.c. 2002

No. 1 machine with 21 heads

No. 1 machine with 12 heads

6" traverse - conical package 5°57-max. diam. 290
mm

Stop at diameter

One motor per head with slow start

Soft start with acceleration ramp 15 sec.

Hank 340 mm - circumference min. 1100 max 1800

Potentiometer for speed adjustment : from 150 to
700 m/m

30% automatic reduction speed per position

Head stop at required diameter

Mechanical slub-catcher with micrometer adjustment

Waxing device

Hank length adjustable per each position

